

# MSTronic Europe

2 Route des Grands Champs, 16130 Genté, France

Tel/Fax: (33) 5 45 83 30 72

email: [craig.paton@mstroniceurope.com](mailto:craig.paton@mstroniceurope.com)

web: <http://www.mstroniceurope.com>

## MIT-4X4


### 4-PORT PoE Injector

#### Features

- Compact and cost effective solution for remote Ethernet terminal
- Plug and Play
- Compliant with 802.3af
- Auto disconnect for over and under voltage
- Independent over current and short circuit protection on each port
- Individual port status indicators
- Support PoE power up to 16.8W for each PoE port
- All materials meet RoHS Directive

#### Specifications

No. of Ports	4 X Legacy Ethernet ports input 4 X PoE ports output
Data Rates	10/100 Mbps
PoE Output	Pin Assignment and Polarity: 4/5 (+), 7/8 (-) Output Power Voltage: -48V Up to 16.8W max. for each PoE port Maximum 67.2W for all PoE ports
Input Power Requirements	AC Input Voltage: 90 to 264 Vac AC Input Current: 1.6A @ 110 Vac /0.8A @ 220 Vac AC Frequency: 47 to 63 Hz
Dimensions	116 mm (W) x 150 mm (D)x 38 mm (H)
Weight	420 g
Indicators	AC Powered (Red) Channel Powered (Green) Channel Alarm (Red)
Environmental Conditions	Operating Ambient Temperature: 0 to 60°C Operating Humidity: Maximum 90%, Non-condensing Storage Temperature: -20 to 80°C Storage Humidity: Maximum 93%, Non-condensing
Certificate	CE, FCC, CB applying
Plastic Case Material	PC



# MSTronic Europe

2 Route des Grands Champs, 16130 Genté, France

Tel/Fax: (33) 5 45 83 30 72

email: [craig.paton@mstroniceurope.com](mailto:craig.paton@mstroniceurope.com)

web: <http://www.mstroniceurope.com>

## Series Models:

MIT-4X4D	4 X 48V/0.35A 802.3af compliant injector
MIT-4X48	4 X 48V/0.5A non-802.3af compliant injector
MIT-4X24	4 X 24V/0.8A non-802.3af compliant injector
MIT-4X18	4 X 18V/1A non-802.3af compliant injector

